

Atur Chambers, 3rd Floor, 2 A, Moledina Road,
 Pune 411 001. India
 Tel: +9120-56090000
 Fax: +9120-27121395/ +9120-26053396
 E-Mail: aquapharm@vsnl.com

Aquapharm Chemicals Pvt. Limited

MAXINOL C5200

Acrylic homopolymer

PRODUCT FEATURES

MAXINOL C5200 is low molecular weight poly-acrylic Acid homopolymer. It is highly effective as dispersant and scale Inhibitor in industrial water treatment, Boiler water treatment as well in all types of water based formulations. It inhibits deposition of Ca / Mg salts (carbonates, sulphates), Barium sulphate and other low solubility salts, which are responsible for depositions of scales on surfaces. The low molecular weight polymer shows good activity over wide range of pH, high hardness and temperature without precipitation. Apart from thermal stability product has good stability to oxidizing agent like chlorine. The product is non-phosphorus, non-foaming dispersant; hence it has good environmental acceptability.

TYPICAL SPECIFICATIONS

Appearance	:	Clear colourless to pale yellow liquid.
Nature	:	Acrylic homopolymer
Grade	:	Partial sodium salt
pH (as is)	:	3.2-4.0
Avg. Molecular Wt.	:	≈4500
Density @ 25 ⁰ C	:	1.18-1.23 gm/cc
Solid Content	:	48.0 ±1.0%
BF Viscosity cP @ 25 ⁰ C	:	250 ± 150 cps

MAJOR BENEFITS

(These are typical values and not the final specifications)

It is very widely used in industrial water treatment as dispersant and scale inhibitor. It inhibits build up of scale by solubility enhancement, crystal growth modification and the dispersion property of the low molecular wet polymer structure.

SAFETY AND HANDLING

MAXINOL C5200 is generally safe but avoid contact with eyes and skin. Do not take internally. Gloves and goggles should be used while handling the product.

STORAGE

MAXINOL C5200 is non-flammable, non-combustible. It should be stored under shade.

PACKING

MAXINOL C5200 is available in 50 Kgs plastic carbouy / 250 Kgs polydrums / 1250 Kgs of IBC